



Tacho V1 Quick Start Version 100




PRECISION
AGRONOMICS AUSTRALIA

www.i4m.tech


admin@precisionag.com.au

Installation – Tractors with ISO Socket



- Plug the harness to the ISO socket
- The ISO socket is for power only, it is not connected to the ISOBUS

Installation – Tractors without ISO Socket




- Connect the power harness to 12volts and ground
- Use switched power (power is off when the tractor key is off)
- If you connect to the battery, unplug the spreader cable when not using the spreader

Power On

- The controller takes 5 seconds to boot up
- LED shows controller status

- No power ○
- Powered on. Nothing is connected to Tacho Wi-Fi. ●
- Powered on. Tablet or phone is connected to Tacho Wi-Fi. ●



Get the Android App

- Connect to the internet
- Scan the code 
- Or Google i4M
- Tap Support > Tacho > Download-App > Select the bottom file
- Tap Open (or go to downloads folder and tap the file)
- Tap Install
- “Trust this app” or “Unsafe app” messages Tap More > Tap Install anyway
- Done



Machine Setup

- From the home screen tap Settings

Hectare counter calibration

- Tap “Fine Tune Hectare Counter”
- Tap “Enter new calibration”
- Enter one of the default values for either 800 or 900 series machines
- Tap “Save”
- Tap “OK”

Swath Width

- Tap “Set Swath Width”
- Enter the swath width
- Tap “Save”
- Tap “OK”

Hopper Empty Sensor

- If a hopper empty sensor is installed
- Tap “Install Hopper Sensor”
- Tap “OK”

Work from your phone

- Operate from your phone without the app
- Put your phone in airplane mode (or turn off mobile data)
- Connect Wi-Fi to TACHO
- Scan the code 
- OR Open your internet browser
- Enter this address 192.168.50.50

